

**Exam : Cisco 640-863**

**Title : Designing for Cisco  
Internetwork Solutions**

**Version : Demo**

1. Which two of these are functions of an access point in a Split MAC Network Architecture?(Choose two.)

- A. EAP Authentication
- B. MAC layer encryption or decryption
- C. 802.1Q encapsulation
- D. Process probe response

**Answer: BD**

2. Lightweight access points are being deployed in remote locations where others are already operational. The new access points are in a separate IP subnet from the wireless controller. OTAP has not been enabled at any locations.

Which two methods can the AP use to locate a wireless controller? (Choose two.)

- A. local subnet broadcast
- B. NV-RAM IP address
- C. DHCP
- D. primary, secondary, tertiary
- E. DNS
- F. master

**Answer: CE**

3. Which of these is the equation used to derive a 64 Kbps bit rate?

- A.  $2 \times 8 \text{ kHz} \times 4\text{-bit code words}$
- B.  $8 \text{ kHz} \times 8\text{-bit code words}$
- C.  $2 \times 4\text{-bit code words} \times 8 \text{ kHz}$
- D.  $2 \times 4 \text{ kHz} \times 8\text{-bit code words}$

**Answer: D**

4. Which two of the following statements represent a preferred wireless LWAPP implementation?(Choose two.)

A. verify open ports for:

Layer 2 LWAPP on ethertype OxABAB

Layer 3 LWAPP on TCP 12222 and TCP 12223

B. verify open ports for:

Layer 2 LWAPP on ethertype OxBBBB

Layer 3 LWAPP on UDP 12222 and UDP 12223

C. verify open ports for:

Layer 2 LWAPP on ethertype OxBABA

Layer 3 LWAPP on UDP 12222 and TCP 12223

D. use of Layer 3 LWAPP is preferred over Layer 2 LWAPP

E. use of Layer 2 LWAPP is preferred over Layer 3 LWAPP

**Answer: BD**

5. Which statement identifies a benefit obtained when using a top-down network design plan?

A. allows quick responses to design requests

B. facilitates design based on previous experience

C. incorporates customer organizational requirements

D. is less time-consuming than using a bottom-up approach

E. provides a more detailed picture of the desired network

**Answer: C**

6. A lightweight access point is added to a working network. Which sequence will it use to associate itself with a wireless LAN controller?

A. master, primary, secondary, tertiary, greatest AP capacity

B. greatest AP capacity, primary, secondary, tertiary, master

C. primary, secondary, tertiary, master, greatest AP capacity

D. primary, secondary, tertiary, greatest AP capacity, master

**Answer: C**

7. Which statement accurately describes one difference between a small office and medium office topology?

A. Small offices commonly use Rapid PVST+ for Layer 3 deployments.

- B. Medium offices commonly use integrated route and switching platforms.
- C. Medium offices use integrated 10/100/1000 interfaces as Layer 2 trunks.
- D. Medium offices use external access switches to support LAN connectivity.

**Answer: D**

8. Which three of these describe the best practice for Cisco wireless outdoor Mesh network deployment?

(Choose three.)

- A. RAP implemented with 20 to 32 MAP nodes
- B. RAP implemented with 20 or fewer MAP nodes
- C. mesh hop counts of 8 to 4
- D. mesh hop counts of 4 or fewer
- E. client access via 802.11b/g and backhaul with 802.11a
- F. client access via 802.11a and backhaul with 802.11b/g

**Answer: BDE**

9. Data link switching is typically used in which Enterprise Campus Module layer?

- A. Server Farm
- B. Campus Core
- C. Building Access
- D. Building Distribution
- E. Internet Connectivity

**Answer: C**

10. Which two statements best describe intradomain route summarization? (Choose two.)

- A. OSPF and RIP automatically summarize at classful network boundaries.
- B. EIGRP and OSPF automatically summarize at classful network boundaries.
- C. EIGRP and RIP automatically summarize at classful network boundaries.
- D. EIGRP and OSPF must be manually configured to summarize at non-classful boundaries.
- E. EIGRP and OSPF automatically summarize at non-classful boundaries.

**Answer: CD**

11. Which Cisco security solution offers protection against "day zero" attacks?

- A. Cisco Adaptive Security Appliance
- B. Cisco Security Agent
- C. Cisco IOS Firewall
- D. Cisco IOS IPS
- E. Cisco Traffic Anomaly Detector

**Answer: B**

12. Which statement can a network designer use to describe route summarization to an IT manager?

- A. It is the grouping of multiple contiguous subnets into one Class A, B, or C IP address to minimize routing table size.
- B. It is the grouping of multiple discontinuous subnets to increase routing performance.
- C. It is the grouping of multiple contiguous networks and advertising as one large network.
- D. It is the grouping of ISP network addresses to minimize the number of routes to the Internet.

**Answer: C**

13. Which three of these are components of the North American Numbering Plan? (Choose three.)

- A. Numbering Plan Area
- B. country code
- C. prefix
- D. zone
- E. line number
- F. trunk channel

**Answer: ACE**

14. Which two statements about designing the Enterprise Data Center Access submodule are correct?

(Choose two.)

- A. Multiport NIC servers should each have their own IP address.
- B. Layer 3 connectivity should never be used in the access layer.

- C. Layer 2 connectivity is primarily implemented in the access layer.
- D. Multiport NIC servers should never be used in the access layer.
- E. Layer 2 clustering implementation requires servers to be Layer 2 adjacent.

**Answer: CE**

15. Which transmission medium should you recommend to this customer?

- A. shielded twisted pair
- B. unshielded twisted pair
- C. multimode fiber
- D. single-mode fiber
- E. wireless

**Answer: D**