

920-136 NCDS

Nortel NCDS - Ethernet Switching Solutions

Practice Exam: 920-136 Exams

Exam Number/Code: 920-136

Exam Name: NCDS - Ethernet Switching Solutions

Questions and Answers: 66 Q&As

([NCDS](#))



Exam : [920-136](#)

"NCDS - Ethernet Switching Solutions", also known as 920-136 exam, is a Nortel certification. With the complete collection of questions and answers, TestInside has assembled to take you through 66 Q&As to your 920-136 Exam preparation. In the 920-136 exam resources, you will cover every field and category in Nortel Certification helping to ready you for your successful Nortel Certification.

Quality and Value for the 920-136 Exam TestInside Practice Exams for Nortel **NCDS** Certification 920-136 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 920-136 Exam.

920-136 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the NCDS product experts, included the current newest 920-136 examination questions.

3. 100% Guarantee to Pass Your NCDS exam and get your NCDS Certification.

If you do not pass the Nortel Certification 920-136 exam (NCDS - Ethernet Switching Solutions) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside 920-136 Q&A ensure you pass the exam at your first try.

TestInside professional provide NCDS 920-136 the newest Q&A, completely covers 920-136 test original topic. With our complete NCDS resources, you will minimize your NCDS cost and be ready to pass your 920-136 tests on Your First Try, 100% Money Back Guarantee included!

[Nortel 920-136](#) Test belongs to one of the NCDS certified test, if needs to obtain the NCDS certificate, you also need to participate in other related test, the details you may visit the [NCDS](#) certified topic, in there, you will see all related NCDS certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about 920-136 exam

920-136 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

920-136 exam questions updated on regular basis

Same type as the certification exams, 920-136 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 920-136 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : Nortel 920-136

Title : NCDS - Ethernet Switching Solutions

1. Internet Group Management Protocol (IGMP) is used by IP Multicast routers to learn about the existence of host group members on their directly attached subnets. Which statement about IGMP is true?

- A. The IP Multicast routers get this information by listening for IP hosts broadcasting IGMP queries and reporting their host group memberships.
- B. The IP Multicast routers get this information by broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.
- C. The IP Multicast routers get this information by recognizing the modified MAC address of a Multicast packet and adding that MAC address to the Multicast tree.
- D. The IP Multicast routers get this information by listening for Multicast Servers broadcasting IGMP queries and listening for IP hosts reporting their host group memberships.

Answer: B

2. A customer is connecting a new remote office to the corporate network. The office will be connected to the network core through a fiber link that terminates at an Ethernet Routing Switch 8600 almost 40km away. It will provide 10/100 Ethernet access for ten people, two printers and one file server at the remote location. The switch that will be installed must meet the requirements below.

The switch must support IEEE 802.3af Power over Ethernet.

Differentiated Services (DiffServ) and advanced IP Policies must be supported to provide IP QoS.

The switch must support the 1000Base-XD Gigabit Interface Connector (GBIC) or Small Form-Factor Pluggable (SFP GBIC) for the uplink connection.

Which switch meets these requirements?

- A. Ethernet Switch 425-24T
- B. Ethernet Switch 470-48T
- C. Ethernet Routing Switch 1648T
- D. Ethernet Switch 460-24T-PWR

Answer: D

3. A customer has a stack of Ethernet Switch 470-48Ts. The uplinks to the network core are via two Gigabit uplink ports from the first Ethernet Switch 470-48T in the stack to a single Ethernet Routing Switch 8600. The links are not part of a MultiLink Trunk (MLT), and spanning tree is running. This results in one of the links always being blocked and recovery time unacceptably long when the active uplink fails. They need to have both links active to increase the bandwidth to the core, and at the same time provide better redundancy.

What is the preferred Nortel solution for the customer?

- A. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and disable spanning-tree on both uplinks.
- B. Move one of the uplinks to another Ethernet Switch 470-48T in the stack and enable Equal Cost Multi-Path (ECMP) on the uplinks.
- C. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and group the two uplinks in a Distributed MultiLink Trunk (DMLT).
- D. Move one of the uplinks to another Ethernet Switch 470-48T in the stack, and ensure that the two uplinks terminate on different modules in the Ethernet Routing Switch 8600.

Answer: C

4. A customer is selecting an Ethernet Routing Switch to be installed in a wiring closet. The switch must support 10 Gbps connections and have redundant power. Which two Ethernet Routing Switches will meet these requirements? (Choose two.)

- A. 1600
- B. 5520
- C. 5530
- D. 8600

Answer: CD

5. A customer is expressing concern about reliability for their single uplink connection to the wiring closet. The switches in the wiring closet support Distributed Multi-Link Trunking (DMLT). What can be done so the Ethernet Routing Switch 8600 can eliminate a single point of failure for the lowest price?

- A. Add a second switch fabric module.
- B. Duplicate the trunk elements in software.
- C. Duplicate the trunks across separate modules using DMLT.
- D. Configure multiple Ethernet Routing Switch 8600s using Split Multi-Link Trunking (SMLT).

Answer: C

6. A customer is selecting an Ethernet Routing Switch to be used to route legacy protocols. It must be able to route IPX traffic and dynamically advertise IPX routes in a network. Which Ethernet Routing Switch will meet these requirements?

- A. 1600
- B. 5500
- C. 8300
- D. 8600

Answer: D

7. An engineer implemented a core network consisting of four Ethernet Routing Switch 8600s and needs the ability to build a redundant core. Which feature would be used to provide redundancy and fail-over times?

- A. Spanning Forest
- B. Multi-Link Trunking
- C. Protocol Based VLANs
- D. Split Multi-Link Trunking

Answer: D

8. A customer is adding fiber support onto an existing 48 port 5510. Their current installation is using all UTP ports on the switch. They need to install two 1000 Base-SX SFPs into the SFP slots. Which statement is true about the requirements for this installation?

- A. The Console port requires SFPs.
- B. Only one 1000 Base-SX GBIC will be supported.
- C. It will require ports 47 and 48 to be unplugged before using SFPs.
- D. It will require the power to the unit is turned off before installing GBICs.

Answer: C

9. A customer is implementing video conferencing devices that require Power over Ethernet (PoE). They are planning to use an Ethernet Routing Switch 8310 chassis for this deployment. They would also like to install 8600 modules in the chassis. Which statement about this customer scenario is true?

- A. Both PoE and 8600 modules are supported in the 8310 chassis.
- B. Neither PoE or 8600 modules are supported in the 8310 chassis.
- C. 8310 chassis does not support PoE, but will support 8600 modules.
- D. PoE could be supplied via the 8310 chassis, but will not support 8600 modules.

Answer: D

10. A carrier needs to support OC-12c (STM-4) and OC-3c (STM-1) on an Ethernet Routing Switch 8600. What is a minimal configuration needed to support this requirement?

- A. one ATM module and no MDAs
- B. one OC-12c/STM-4 module and one OC-3c/STM-1 module
- C. one OC-12c/STM-4 ATM MDA and one OC-3c/STM-1 ATM MDA on an ATM module
- D. one OC-12c/STM-4 ATM MDA on the first ATM module and one OC-3c/STM-1 ATM MDA on the second ATM module

Answer: C

[More 920-136 Information](#)

Related 920-136 Exams

[920-165](#) *NCDS-Contact Center Ris.6.0 Exam*

[920-141](#) *NNCDS-Communication Server(cs)1000 release 4.0*

[920-256](#) *Nortel VPN Router Ris.7.0 Solutions(NCDS)*

[920-136](#) *NCDS - Ethernet Switching Solutions*

[920-203](#) *nncds passport 7000/15000*

[920-242](#) *nncds-contivity vpn switch*

[920-125](#) *NNCDS Succession BCM 3.0 Exam*

[920-209](#) *NCDS-Multiservice Switch 7400/15000/20000*

[920-124](#) *NNCDS -Ethernet Switching Exam*

Other Nortel Exams

| | | | | | | | |
|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| <u>920-105</u> | <u>920-361</u> | <u>920-806</u> | <u>920-021</u> | <u>922-061</u> | <u>922-102</u> | <u>922-054</u> | <u>920-128</u> |
| <u>920-246</u> | <u>920-191</u> | <u>920-336</u> | <u>920-465</u> | <u>922-111</u> | <u>920-176</u> | <u>920-181</u> | <u>920-451</u> |
| <u>920-433</u> | <u>920-322</u> | <u>920-804</u> | <u>920-327</u> | | | | |